

In the claims:

Please amend the claims as follows:

1. (currently amended) An industrial robot for moving an object in space comprising a stationary platform (3), a movable platform (31) adapted for supporting the object, and a first (A), a second (B) and a third (C) arm to which the platforms are joined, wherein the first arm comprises a first actuator (10), a first supporting arm (13) influenced by the first actuator and rotatable around a first axis, and a first linkage (16, 17), the second arm comprises a second actuator (11), a second supporting arm (14) influenced by the second actuator and rotatable around a second axis, and a second linkage (18, 19), and the third arm comprises a third actuator (12), a third supporting arm (15) influenced by the third actuator and rotatable around a third axis, and a third linkage (20, 21), ~~characterized in that~~ wherein the first and third axes are arranged parallel and that the second supporting arm is freely journalled around a transverse axis that is substantially arranged in a plane normal to the second axis.

2. (currently amended) ~~An~~ The industrial robot according to claim 1, ~~characterized in that~~ wherein the second supporting arm comprises a bearing (12A) and is adapted to rotate in a plane intersecting the movable platform.

3. (currently amended) ~~An~~ The industrial robot according to claim 1 or 2, ~~characterized in that~~ claim 1, wherein the first and third linkages comprise a triangle with the base journalled in the respective supporting arm.

4. (currently amended) ~~An~~ The industrial robot according ~~any of the preceding claims,~~
~~characterized in that~~ to claim 1, wherein the third linkage comprises a triangle where the base is
journalled in the movable platform.

5. (currently amended) ~~An~~ The industrial robot according ~~claims 1 to 3, characterized in~~
~~that~~ to claim 1, wherein the third linkage comprises a locked double link.

6. (currently amended) An industrial robot for moving an object in space comprising a
stationary platform, a movable platform adapted for supporting the object, and a first, a second
and a third arm to which the platforms are joined, wherein the first arm comprises a first
actuator, a first supporting arm influenced by the first actuator and displaceable along a first
path, and a first linkage, the second arm comprises a second actuator, a second supporting arm
influenced by the second actuator and displaceable along a second path, and a second linkage,
and the third arm comprises a third actuator, a third supporting arm influenced by the third
actuator and displaceable along a third path, and a third linkage, ~~characterized in that~~ wherein the
first and third paths are arranged parallel and that the second supporting arm is freely journalled
around a transverse axis that is substantially arranged at right angles to the second path.

7. (currently amended) A method for manufacturing an industrial robot, with which an
object is moved in space, comprising providing the industrial robot with a stationary platform, a
movable platform adapted for supporting the object, and a first, a second and a third arm to
which the platforms are joined, wherein the first arm is brought to comprise a first actuator, a

first supporting arm influenced by the first actuator and rotatable around a first axis, and a first link- age, the second arm is brought to comprise a second actuator, a second supporting arm influenced by the second actuator and rotatable around a second axis, and a second linkage, and the third arm is brought to comprise a third actuator, a third supporting arm influenced by the third actuator and rotatable around a third axis, and a third linkage, ~~characterized in that~~ wherein the first and third axes are arranged parallel and that the second supporting arm is arranged freely journaled around a transverse axis that is substantially arranged at right angles to the second axis.

8. (currently amended) Use of an industrial robot according to ~~claims 1-6, or a method according to claim 7~~ claim 1 during laser cutting.

9. (new) Use of a method according to claim 7 during laser cutting.